

June, 2015

3M™ Premium High Temperature Masking Tape 2393

Product Description

3M™ Premium High Temperature Masking Tape 2393 is a smooth, heavy duty, mini-crepe, premium high temperature masking tape. It is specifically designed for those applications where easy removal after bake is important. This masking tape offers excellent paint mask performance with high solids paints and clear coats used in the transportation industry.



Product Features

- Can be certified to ASTM D-6123/D-6123M-97 upon request. (replaces obsolete PPP-T-42C, Type I, and (CID-A-A-883B).
- The adhesive offers excellent adhesion to and easy removability from both metal and plastic substrates.
- Excellent high temperature performance that holds firmly under heat strain yet removes cleanly.
- The smoothness of the backing makes this tape very “user friendly.”
- Rubber adhesive with instant adhesion that sticks easily and allows fast application.
- Excellent holding power that resists lifting or curling and helps reduce rework.
- Conformability and easy handling that reduces time involved.
- Special backsize treatment that controls unwind, and helps reduce waste.
- The balanced construction with a stronger backing gives this tape easy removal properties without slivering.
- Low unwind reduces workers’ fatigue.
- Tape may become difficult to remove if subjected to prolonged outdoor exposure

3M™ Premium High Temperature Masking Tape 2393

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	Tan		
Total Tape Thickness	0.185 mm	7.6 mil	ASTM D3652
Backing	Smooth mini-crepe paper treated with a heat resistant saturant.		
Adhesive	Rubber		

Typical Performance Characteristics

Property	Values		Method	Substrate
Peel Adhesion	3.6 N/cm	32 oz/in	ASTM D3330	Stainless Steel
Tensile Strength	49 N/cm	448 oz/in	ASTM D3759	
Elongation at Break	11 %		ASTM D3759	
Temperature Use Range	30 minutes up to 163 °C	30 minutes up to 325 °F		

Available Sizes

Property	Values		Notes
Standard Roll Length	55 m	60 yd	Available in metric widths (eg, 24 mm corresponds to 1 inch).

3M™ Premium High Temperature Masking Tape 2393

Storage and Shelf Life

Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton. To obtain best performance, use within 18 months from date of manufacture.

Trademarks

3M is a trademark of 3M Company.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all-3m-products/~/%3M-Premium-High-Temperature-Masking-Tape-2393?N=5002385+3293240939&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=2393

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Premium High Temperature Masking Tape 2393

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M™ Premium High Temperature Masking Tape 2393



3M United States
3M Center
St. Paul, MN 55144-1000
800-362-3550
www.3M.com

Please recycle.
© 3M 2020. All Rights Reserved.

The brands listed above are trademarks of 3M